

## Ludlow

**GENERAL SPECIFICATIONS** 

WEIGHT (LINEAR YARD) 21/22 oz per linear yard

WIDTH 54"

COMPOSITION 100% Polyester

■ PIECE DYED ☐ YARN DYED ☐ FIBER DYED

□ DOBBY □ JACQUARD □ PILE

YARN PER INCH 50.0 EPI, 58.9 PPI

YARN SIZE T1000D Warp, T1000D Fill

BACKING

CLEANING CODE SW, Spot clean with upholstery shampoo, foam from a mild detergent,

or a mild dry cleaning solvent. Do not saturate with liquid. Pile fabrics may require brushing to restore appearance. Cushion cover should not

be removed and dry cleaned.

PHYSICAL PERFORMANCE SPECIFICATIONS

ABRASION RESISTANCE 100,000+ Double Rubs\* ASTM D4157-13
BREAKING STRENGTH 536 Warp, 384 Fill ASTM D5034-09
BRUSH PILL Class 4.5 ASTM D3511
CROCKING RESISTANCE 4.5 Dry, 4.5 Wet AATCC 8-20013

COLORFASTNESS TO LIGHT Class 4.5 AATCC 16.3-2012, Option 3

SEAM SLIPPAGE 33.6 Warp, 26.7 Fill ASTM D4034-92 TEAR STRENGTH: TONGUE TEAR 113.8 Warp, 109.0 Fill ASTM D2261-13

\*Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan.

## FLAME RETARDANCY SPECIFICATIONS

CALIFORNIA TECHNICAL BULLETIN 117:13 Pass
UFAC CLASS I Pass
NFPA 260 Pass

## REDUCED ENVIRONMENTAL IMPACT

THIS PRODUCT DOES NOT POSE ANY EXPOSURE RISKS ASSOCIATED WITH THE CHEMICALS IN PROP 65
NO ADDED FLAME RETARDANT CHEMICALS - AB2998 COMPLIANT
NO ADDED ANTI-BACTERIAL / ANTI-MICROBIAL CHEMICALS
LEAD / HEAVY METAL FREE
BPA FREE / TRIS FREE / FORMALDEHYDE FREE
DOES NOT CONTAIN CONFLICT MINERALS









\*ACT® Registered Certification Marks